

CUSTOMER SPECIFICATION

		Nominal	Minimum	Maximum	Test Methods	
Thickness (micron)		45	38	52	COV-E-201	
Width (mm)	0-179	any	ES		COV-E-200	
	180-299		-3	+15		
	300-374		-4	+18		
	375-474		-5	+20		
	475-up		-6	+25		
Length (m)	0-299	any	-5	+15	COV-E-217	
	300-499		-8	+20		
	500-799		-10	+25		
	800-up		-15	+30		
Width (mm)	0-99	any	TS		COV-E-200	
	100-179		-3	+3		
	180-299		-3	+3		
	300-350		-5	+5		
	351-399		-5	+7		
	400-499		-6	+17		
	500-599		-8	+21		
	600-699		-10	+25		
	700-799		-11	+29		
	800-899		-13	+34		
	900-999		-15	+38		
	1000-1099		-17	+43		
	1100-1199		-18	+47		
	1200-1299		-20	+52		
	1300-1399		-22	+56		
	1400-1499		-24	+61		
	1500-1599		-26	+65		
1600-1699	-28	+70				
1700-1800	-30	+74				
Length (m)	0-179	any	-3	+15	COV-E-217	
	180-299		-4	+18		
	300-374		-5	+20		
	375-474		-6	+25		
	475-up		-8	+30		
Modulus (kg/cm ²)	LD	2400		3200	COV-E-212	
	TD	2400		3200		
Elongation (%)	LD	120	80		COV-E-211	
	TD	140	100			
Tensile (kg/cm ²)	LD	800	500		COV-E-211	
	TD	800	500			
Shrink (%) at 85°C	LD	39	34		COV-E-209	
	TD	47	41			
Haze (%)		7		11	COV-E-340	
Gloss (g.u.)			100		COV-E-341	
O ₂ (cm ³ /m ² ,24h,bar)	at 23°C, 0% RH	20		50	COV-E-342	
CO ₂ (cm ³ /m ² ,24h,bar)	at 23°C, 0% RH			150	COV-E-343	
TRANSPORTATION and STORAGE						
Recommended Temperature			2°C	25°C		
Recommended R.H				80%		
Recommended Storage period				12 Months		
Tubing for Loaders	Width (mm)	any	The same as for ES Bags		COV-E-200	
	Length (mm)	any	-0	+20		
	Tubing Splices			3		
	Roll Edge stepping (Roll width)	0-374		0	+10	
		375-up		0	+14	
Recommended Storage period (Months)	Plain	12		12		
	Printed	3		3		

NOTE

All statements or recommendations are based on data knowledge considered to be true and accurate at the time of printing but should be verified by the user. Since the condition of use is beyond our control we do not warrant the completeness or suitability for any intended purpose of any statement or recommendation, or the result to be obtained. Please read all the statements or recommendations in conjunction with our conditions of sale including those limiting warranties and remedies which apply to all goods and services by us. National or local legal requirements relating to health safety at work and the protection of the environment shall be applicable in all cases.

VERSION: n° 10

DATE: 5-Jan-2023

ISSUED BY:

MOlek

Monika Olek

Customer Technical Documentation Administrator

APPROVED BY:

Baran

Andrzej Baran

Executive Director Quality Europe